




**Important:**

- Nu-Wall is a hollow profile and requires packers to prevent crushing under pressure

**General note:**

- Cladding fixings omitted for clarity

**Cavity batten note:**

- 20mm single castellated timber battens required for all Nu-Wall installations.
- Batten to have 15° slope for moisture egress
- Allow 6mm gap between vertical and horizontal battens
- Sill and head battens to be max. 500mm with a 6mm gap to each segment
- 18mm single castellated battens are available from Nu Wall for all vertical applications to wall junctions and jambs
- Proprietary Nu-Wall Alibat is available as an alternative when a structural non-combustable cavity batten is required



|  |                                                                                                                                                                                        |  |                    |                  |
|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--------------------|------------------|
|  | Nu-Wall cladding horizontal on cavity                                                                                                                                                  |  | NW-HOC-025.02      |                  |
|  | Typical deck to wall junction                                                                                                                                                          |  | Drawn by: Nu-Wall  | Date: 02/07/2025 |
|  | © 2021 copyright in this document is the property of Nu-Wall Aluminium Cladding Limited. All rights reserved. Nu-Wall is a registered trademark of Aluminium Product Brands NZ Limited |  | Checked by: RL, GT | Scale: 1:2 @ A4  |